



Control and Sizing of Microgrids: Current Challenges, Control Approaches, and Future Direction

¹Abba Muhammad Adua, ²Rabiu B. Ahmad, ³I. I. Alabi, ³A. I. Araga, ⁴Yau Alhaji Samaila, ¹Umar M. Jajere

¹Department of Electrical and Electronics Engineering,
Kebbi State University of Science and Technology, Aliero,

²Department of Aerospace Engineering,
Air Force Institute of Technology, Kaduna, Nigeria

³Department of Electrical and Electronics Engineering,
Nigerian Defence Academic (NDA) Kaduna,

⁴Department of Electrical and Electronics Engineering
University of Maiduguri, Borno State

ABSTRACT

Microgrids have emerged as a vital component of modern energy systems, offering localized generation and distribution capabilities that enhance grid resilience and sustainability. However, the effective control and sizing of microgrids present intricate challenges that demand innovative approaches and future-focused strategies. The challenges in controlling and sizing microgrids primarily revolve around the integration of diverse energy resources, load dynamics, and the need for seamless transition between grid-connected and islanded modes. Accurate sizing of components, such as renewable energy sources, energy storage systems, and control devices, is pivotal for optimizing microgrid performance. In response to these challenges, a variety of control approaches have been developed. Hierarchical control structures, including primary, secondary, and tertiary control layers, enable coordinated control of microgrid components. Advanced optimization techniques, such as model predictive control and distributed control, enhance the efficiency and reliability of microgrid operations. In conclusion, the control and sizing of microgrids represent a dynamic research domain with multifaceted challenges and evolving control paradigms. Addressing these challenges and embracing novel control strategies will be pivotal in realizing the full potential of microgrids, fostering energy sustainability, and contributing to the transformation of future energy grids. This abstract provides a foundational understanding of the current state, emerging trends, and potential research directions in the domain of microgrid control and sizing.

ARTICLE INFO

Article History

Received: March, 2023

Received in revised form: June, 2023

Accepted: July, 2023

Published online: September, 2023

KEYWORDS

Microgrid Systems, Control, Sizing,
Renewable Energy Integration

INTRODUCTION

Microgrids represent a transformative approach in the quest for more resilient, efficient, and sustainable energy systems. As self-sufficient energy systems that can operate independently or in conjunction with the main power grid, microgrids integrate distributed energy resources (DERs) such as solar panels, wind turbines, and energy storage systems. This integration offers significant

advantages in terms of energy security, reliability, and environmental sustainability. However, the control and sizing of microgrids pose complex challenges that require sophisticated approaches to ensure optimal performance.

The growing penetration of renewable energy sources in microgrids is a double-edged sword. On one hand, it reduces dependence on fossil fuels and decreases greenhouse gas

Corresponding author: Abba Muhammad Adua

✉ abbamuhammadadua@yahoo.com

Department of Electrical and Electronics Engineering, Faculty of Engineering, Kebbi State University of Science and Technology, Aliero.

© 2023. Faculty of Technology Education. ATBU Bauchi. All rights reserved

emissions, aligning with global sustainability goals. On the other hand, the intermittent and variable nature of renewable energy sources introduces significant uncertainties in power generation. According to [1], managing these uncertainties is one of the primary challenges in microgrid control, as it directly impacts the stability and reliability of the power supply.

Energy storage systems, particularly batteries, play a critical role in addressing the intermittency of renewables. However, as highlighted by [2], the high costs, limited lifespan, and recycling issues of current battery technologies present substantial hurdles. The integration and optimization of these storage systems within microgrids necessitate advanced control and sizing strategies to balance performance, cost, and longevity.

Economic viability is another pressing concern. While microgrids offer long-term benefits such as reduced operational costs and enhanced energy security, the initial capital investment is often prohibitively high. The paper [3] emphasizes the need for innovative financial models and cost-effective technological solutions to make

microgrids more accessible and attractive to both urban and rural communities.

To address these multifaceted challenges, a variety of control approaches have been developed. Hierarchical control structures, as described by [4], provide a robust framework for managing the different layers of microgrid operations, from real-time local control to higher-level economic dispatch. Decentralized control methods, such as multi-agent systems and peer-to-peer energy trading, offer scalable and resilient alternatives by distributing control functions across multiple nodes, thereby enhancing the microgrid's adaptability and fault tolerance[5].

The advent of artificial intelligence (AI) and machine learning (ML) is revolutionizing microgrid control. The paper [6] illustrates how AI-based predictive models and reinforcement learning algorithms can optimize energy management and decision-making processes, significantly improving efficiency and reducing costs. These technologies enable microgrids to adapt dynamically to changing conditions, thereby enhancing their overall performance and reliability.




Figure 1.1 Basic structure of an autonomous MG [7]

LITERATURE REVIEW

The literature on the control and sizing of microgrids has evolved significantly over the past decade, reflecting the rapid advancements in renewable energy technologies, energy storage

solutions, and smart grid innovations. This review synthesizes recent, reliable, and relevant studies to provide a comprehensive understanding of the current challenges, control approaches, and future directions in microgrid systems [12].

Corresponding author: Abba Muhammad Adua

✉ abbamuhammadadua@yahoo.com

Department of Electrical and Electronics Engineering, Faculty of Engineering, Kebbi State University of Science and Technology, Aliero.
 © 2023. Faculty of Technology Education. ATBU Bauchi. All rights reserved



Current Challenges

Microgrids face numerous challenges, primarily driven by the integration of renewable energy sources such as solar and wind. These sources are inherently intermittent and unpredictable, leading to stability and reliability issues in microgrid operations. According to a study by [13], managing the variability and uncertainty of renewable energy generation is one of the foremost challenges in microgrid control. Moreover, the high initial costs and economic viability of microgrids remain critical concerns, as highlighted by [14], who emphasize the need for cost-effective solutions to enhance the adoption of microgrids in both urban and rural areas. Energy storage is another pivotal challenge in microgrid management. The authors of [15] discussed the role of

Control Approaches

Various control strategies have been proposed to address these challenges, with a focus on enhancing the stability, reliability, and economic performance of microgrids. Hierarchical control structures are widely recognized for their effectiveness in managing the complex dynamics of microgrids. The paper [16], described a three-layer hierarchical control system comprising primary, secondary, and tertiary controls, each responsible for different aspects of microgrid management. This layered approach allows for real-time control at the local level, coordinated control at the microgrid level, and optimal economic dispatch at the higher level.

Decentralized control methods have also gained prominence due to their scalability and robustness. An in-depth study by [17] explores decentralized control techniques such as multi-agent systems and peer-to-peer energy trading, which facilitate autonomous decision-making and improve resilience against failures.

Artificial intelligence (AI) and machine learning (ML) techniques are increasingly being integrated into microgrid control systems. According to [18], AI-based predictive models can forecast energy generation and demand with high accuracy, enabling more efficient energy management and reducing operational costs.

Furthermore, reinforcement learning algorithms are being employed to optimize real-time control decisions, enhancing the adaptability of microgrids to changing conditions.

Optimization Techniques

Optimization plays a crucial role in the design and operation of microgrids. Linear programming (LP) and mixed-integer programming (MIP) are traditional optimization methods widely used for unit commitment and economic dispatch problems. Recent advancements, as discussed by [19], have incorporated non-linear programming (NLP) and dynamic programming (DP) to address the non-linearities and complexities in microgrid operations.

Stochastic optimization techniques have been developed to handle uncertainties in renewable energy generation and load demand. The paper [9] present stochastic programming models that consider various scenarios and probabilities, providing robust solutions that enhance the reliability of microgrids under uncertain conditions. Heuristic methods, including genetic algorithms (GA) and particle swarm optimization (PSO), have been applied to solve complex optimization problems in microgrids. A study by [10] demonstrates the effectiveness of these methods in optimizing the sizing and placement of distributed energy resources (DERs), thereby improving the overall efficiency and performance of microgrids.

The future of microgrid research is oriented towards the development of more advanced and adaptive control algorithms. With the increasing penetration of AI and IoT technologies, real-time monitoring and predictive control are expected to become more sophisticated. The paper [11] suggest that the integration of blockchain technology could enhance the security and transparency of energy transactions within microgrids, fostering greater trust and participation among stakeholders. Furthermore, advancements in energy storage technologies, such as solid-state batteries and supercapacitors, are anticipated to address the current limitations of battery systems. Research

Corresponding author: Abba Muhammad Adua

✉ abbamuhammadadua@yahoo.com

Department of Electrical and Electronics Engineering, Faculty of Engineering, Kebbi State University of Science and Technology, Aliero.
© 2023. Faculty of Technology Education. ATBU Bauchi. All rights reserved

by [20] indicates that these technologies could offer higher energy densities, longer lifespans, and faster charging times, significantly boosting the performance and economic viability of microgrids.

In conclusion, the literature review highlights the significant progress made in the control and sizing of microgrids while also identifying ongoing challenges and opportunities for future research. By leveraging advanced control strategies, optimization techniques, and emerging technologies, microgrids can play a crucial role in achieving sustainable and resilient energy systems.

Microgrid Design Optimization Criteria

Different design criteria are used to attain the best design outcomes in both grid-connected and standalone microgrids. Researchers have used a variety of optimization

objective functions, sometimes referred to as design criteria, over time to evaluate microgrid systems.

Power electronics, distributed generators (DGs), energy storage systems, loads, and communications are only a few of the technologies used by microgrids [14]. Power electronics, distributed generators (DGs), energy storage systems, loads, and communications are only a few of the technologies used by microgrids [14]. Utilizing MGs has advantages that include:

1. reduced transmission and distribution losses,
2. improved power supply availability despite individual unit failures and
3. The potential to include extra management or control services is a possible solution to the difficulties associated with intermittent DERs [21].



Figure 2:1 Microgrid configuration

The importance of Microgrid

Microgrids (MGs) were originally designed with the intention of self-supplying their locations, but this situation quickly altered as it was realized that transactional approaches could be deliberately used to achieve financial advantages [22]. End users receive a considerable return from the MGs in the form of low-cost electricity users, less reliance on the power grid, decreased service fees, and income from injecting surplus electricity into the grid [11].

GRID-CONNECTED MICROGRID OVERALL SCHEME

Figure 3.1 depicts the general layout of the proposed Grid-connected MG. In this study, MG is made up of conventional diesel engine (CDE) sources, demand response (DR) models, and consumers with renewable energy sources including photovoltaic (PV) generator sources and wind turbine (WT) generator sources [23], [24].

THE STRATEGY OF POWER MANAGEMENT

The operating strategies, or the coordinated controls among the many distributed

Corresponding author: Abba Muhammad Adua

✉ abbamuhammadadua@yahoo.com

Department of Electrical and Electronics Engineering, Faculty of Engineering, Kebbi State University of Science and Technology, Aliero.
© 2023. Faculty of Technology Education. ATBU Bauchi. All rights reserved

energy systems, are what determine how economically and technically effective microgrids are:

Microgrid Optimal Sizing Methods

Researchers developed and used a variety of optimization strategies, all of which

aimed to achieve the aforementioned goals functions, or design criteria described above. The RE system design can employ optimization at any point to identify the best operating requirements while addressing all roadblocks.




Figure 2.2: Grid-Connected MG Scheme with DR mode




Figure 2.3: The sizing optimization methods

METHOD AND MATERIALS

To carry out this review on a systematic approach is adopted. Initially, a comprehensive


search is conducted in major academic databases such as IEEE Xplore, ScienceDirect, and Google Scholar to identify relevant peer-reviewed journal

Corresponding author: Abba Muhammad Adua

✉ abbamuhammadadua@yahoo.com

Department of Electrical and Electronics Engineering, Faculty of Engineering, Kebbi State University of Science and Technology, Aliero.

© 2023. Faculty of Technology Education. ATBU Bauchi. All rights reserved



articles, conference papers, and industry reports published in the last decade. Keywords such as "microgrid control," "microgrid sizing," "renewable energy integration," "energy storage management," and "grid stability" are used to refine the search. Each selected paper is then meticulously reviewed to extract information on the current challenges faced by microgrids, various control strategies employed, and the optimization techniques applied. Special focus is placed on identifying gaps in the existing research and potential areas for future study.

OVERVIEW OF THE DETAIL ASSOCIATED WITH CONTROLLING, OPTIMIZING, AND SIZING SYSTEMS, AS WELL AS ENERGY MANAGEMENT

This section covered the topics of hybrid renewable energy system sizing, control, optimization, and energy management.

Sizing in hybrid renewable energy system

Hybrid renewable energy systems have evolved as an effective way to handle the sporadic and variable nature of individual renewable energy sources as the demand for clean and sustainable energy sources keeps rising. Hybrid systems must be properly sized to perform at their peak, have a consistent power source, and be as economical as possible. In addition to optimization analyses, software has been developed for designing and assessing the performance of microgrids. HOMER is the most widely used simulation software for creating microgrids, followed by HOGA/IHOGA, HYBRID2, and HYBRIDS.

To determine the generators' capacity, it is crucial to size the hybrid system [25]. Without proper sizing, the system runs the danger of being undersized or oversized [26]. The measurement of real load and step time to precisely account for changes presents the most challenges. According to ref. [27], The majority of researchers use average hours, days, or months as data samples. There are two types of size techniques: the first uses software, while the second uses conventional techniques [28], [29].

Sizing using Software

To size hybrid systems, a variety of commercial applications are available. The majority of these applications, such as RET Screen, iHOGA (Hybrid Optimization by Genetic Algorithm), INSEL (Integrated Simulation Environment Language), HOMER (Hybrid Optimization Model for Electric Renewable), and other software, run on Windows computers and use the Visual C++ programming language [30]. For sizing hybrid systems based on diesel generators, solar generators, and wind turbines with storage systems (batteries) for large supply, authors in [31] employed HOMER software. The goal of this study is to employ a hybrid system that is less expensive and produces less carbon dioxide. The system localized cost between 9,3 and 12,6 cents per kWh with 43.9% coming from global production and renewable resources is the best economic outcome after simulation [32].

Sizing using traditional methods

There are four primary conventional approaches for sizing and they are as follows:

1. Analytical method;
2. Iterative approach;
3. Probabilistic method;
4. Artificial intelligence methods.

Using Analytical method

According to this method's definition of hybrid system size as a function of viability, the hybrid system is taken into account as a tool for a numerical model [33]. A study for a hybrid system utilizing an analytical method, with a solar generator and a wind turbine as its constituent parts, was published by [34]. The goal is to look at how to make the hybrid system's water efficiency more efficient.


Using Iterative approach

This approach is a recursive algorithm program that terminates when the ideal system design is reached [30]. This technique was used by [35] to size a standalone hybrid system that combined batteries, solar PV, and wind power for supply to a remote village. This study's goal is to

Corresponding author: Abba Muhammad Adua

✉ abbamuhammaddua@yahoo.com

Department of Electrical and Electronics Engineering, Faculty of Engineering, Kebbi State University of Science and Technology, Aliero.
© 2023. Faculty of Technology Education. ATBU Bauchi. All rights reserved



create a system with low costs and excellent reliability [36].

Using Probabilistic method

The impact of wind speed isolation and modifications to the system design are taken into consideration by probabilistic approaches to the size of an integrated system [37]. Even though it is one of the most often utilized size approaches, studies indicate that it might not be the optimal approach to take [38]. Using the Probability-Power Pinch Analysis (P-PoPA) approach, [39] developed an algorithm for sizing solar photovoltaic, wind turbine, biomass, and batteries. The result demonstrates that the energy storage system's power rating and capacity are maximized while its reliance on external energy sources is minimized [39].

Using Artificial Intelligence Methods

The definition of artificial intelligence given by their review article "A review on configurations, control, and sizing methodologies of hybrid power systems" was as follows: "Artificial intelligence is a term that in its broadest sense would mean the ability of a machine to perform similar kinds of functions that characterize human thought" [40].

COMPARISON OF SEVERAL SIZE TECHNIQUES

The simplicity and speed of traditional methods render them limited in terms of performance and analysis [41]. The artificial intelligence methodology can get over this challenge since it uses a multi-objective function to handle complex problems. This problem can be solved using an iterative approach when this method is based on a simple algorithm using the recursive process to achieve the best size system, but the disadvantage of this approach is that it ignores some crucial parameters. Based on a simple numerical model, the analytical method sizes hybrid systems quickly with low flexibility [42]. Artificial intelligence is the best option for all complex procedures, without limitations and with good outcomes when compared to other ways. The most challenging aspect of this topic is the

complexity codes utilized in this algorithm promising areas, while exploitation focuses on refining the current best solution. [48], [51].

UTILIZING HYBRID RENEWABLE ENERGY SYSTEMS IN MICROGRIDS THROUGH OPTIMIZATION

Optimization methods have become crucial in designing and managing hybrid renewable energy systems in microgrids [36]. As the demand for clean and sustainable energy sources continues to rise, microgrids, which are localized grids that can operate independently or in conjunction with the main power grid, have gained significant attention [43]. These microgrids often integrate multiple renewable energy sources, such as solar, wind, and hydro, along with energy storage systems and conventional energy sources to ensure a stable and reliable power supply [44]. Hybrid renewable energy systems in microgrids present unique challenges due to the intermittent nature of renewable energy sources and varying energy demands. To maximize the utilization of renewable energy and optimize the system's performance, various optimization methods are employed [45]. These methods leverage mathematical algorithms and models to determine the optimal configuration, sizing, and operation strategies of the different components within the microgrid [46], [47].

Optimization Methodologies

As described by ref [25] Metaheuristic algorithms are problem-solving techniques that guide the search for optimal or near-optimal solutions by iteratively exploring the solution space. They are not problem-specific and can be applied to a wide range of optimization problems. Metaheuristic algorithms strike a balance between exploration and exploitation. Exploration refers to searching a wide range of solutions to discover new promising areas, while exploitation focuses on refining the current best solution. [48], [51].

Using Classical methods

Classical methods of optimization refer to a set of established and widely used techniques for solving optimization problems in mathematics,

Corresponding author: Abba Muhammad Adua

✉ abbamuhammaddua@yahoo.com

Department of Electrical and Electronics Engineering, Faculty of Engineering, Kebbi State University of Science and Technology, Alfero.
© 2023. Faculty of Technology Education. ATBU Bauchi. All rights reserved



engineering, economics, and other fields [29]. These methods rely on mathematical principles and algorithms to find the best possible solution to a given problem [29]. According to [52], the classical approach is a method that employs differential calculation to arrive at the best possible outcome. These strategies were rarely used by researchers because of their constrained spatial optimization. The linear programming model (LPM) [8], mixed integer linear programming (MILP) [53], dynamic programming (DP) [54], and nonlinear programming (NLP) are a few examples of classical optimization methods [55].

Using Artificial methods

Artificial methods refer to techniques or approaches that are designed and implemented by humans to achieve a specific goal or outcome [29]. In various fields, artificial methods have been developed and applied to advance scientific research, improve efficiency, and address challenges in areas such as medicine, engineering, computer science, and environmental science. Here are some examples of artificial methods in different domains: Artificial Intelligence (AI) [56]. Machine learning, a subset of AI, enables computers to learn from data and make predictions or decisions without explicit programming [29]. Deep learning, a type of machine learning, uses neural networks with multiple layers to process complex information, such as images or natural language [57]. The ongoing advancements in technology and human ingenuity continue to drive the development of new and innovative artificial methods, expanding the possibilities for scientific discovery, problem-solving, and human progress [58].

1. Using Genetic algorithm

The term "genetic algorithm" is now used to refer to things that have little to do with John Holland, the man who invented it. A hybrid system including a solar generator, wind turbine, diesel generator, and storage system (battery) for Senegal's remote locations was designed and optimized by [59] using a genetic algorithm. There are two goals for this study: economic and environmental. Getting the system's leveled cost

as low as possible is the primary goal, and cutting carbon dioxide emissions is the second. Genetic algorithms have been successfully applied in various fields, including optimization, machine learning, scheduling, and design problems [57]. A genetic algorithm is a computational optimization technique inspired by the process of natural selection and evolution [60], [61].

2. Fuzzy logic

Fuzzy logic is a mathematical framework that deals with uncertainty and imprecision in decision-making and reasoning. It is a form of logic that allows for the representation and manipulation of vague or ambiguous information [4]. Fuzzy logic is a branch of much-valued logic that deals with reality [24]; [28]. Leonora in [28] defined fuzzy logic in a modest sentence and inscribed: "Fuzzy logic deals with realism and it is a form of much-cherished logic" [26], [62].

3. Particle swarm optimization

Optimizing swarms of particles (PSO):- In this method, each particle (or animal) represents a potential solution in a three-dimensional space with continuously changing positions and speeds [55], [63]. The method depends on the movement of fish or birds. A hybrid system based on solar and concentrator solar photovoltaic with battery was optimized by [64] using this algorithm in conjunction with a genetic algorithm. When compared to other systems and strategies, the obtained results demonstrate optimization in both technical parameters. PSO involves simulating a swarm of particles in a multi-dimensional search space [58]. Overall, PSO is a versatile and effective optimization technique that mimics the collective behavior of swarms. It offers a balance between exploration and exploitation, making it a popular choice for various optimization problems.

4. Pelican Optimization Algorithm (POA)

The Pelican Optimization Algorithm (POA) is a metaheuristic optimization algorithm inspired by the behavior of pelicans, specifically their foraging and hunting strategies. It was

Corresponding author: Abba Muhammad Adua

✉ abbamuhammaddua@yahoo.com

Department of Electrical and Electronics Engineering, Faculty of Engineering, Kebbi State University of Science and Technology, Aliero.
© 2023. Faculty of Technology Education. ATBU Bauchi. All rights reserved



developed to solve complex optimization problems across various domains. The algorithm mimics the social behavior and movement patterns of pelicans to efficiently explore the search space and find optimal or near-optimal solutions.

Here are some key details about the Pelican Optimization Algorithm:

1. Foraging Behavior: Pelicans are known for their cooperative foraging behavior. They work together to encircle and capture fish in a group. Similarly, in the Pelican Optimization Algorithm, a population of solutions (pelicans) collaboratively searches for the best solution.
2. Movement and Exploration: Pelicans exhibit a combination of short and long-range movements during their foraging process. These movements enable them to explore new areas while exploiting the regions with a higher probability of finding food. The POA utilizes a similar mechanism by employing both exploration and exploitation strategies to navigate the search space effectively.
3. Pelican Positions: In the algorithm, the positions of the pelicans represent potential solutions to the optimization problem. Each pelican's position is a vector of decision variables that encode a particular solution.
4. Fitness Evaluation: The fitness of each pelican is determined by evaluating its position in the problem's objective function. The objective function represents the optimization criterion or goal that needs to be maximized or minimized.
5. Communication and Collaboration: Pelicans communicate and collaborate to improve their foraging success. Likewise, the Pelican Optimization Algorithm incorporates a mechanism for information exchange between pelicans. This helps in sharing

- promising solutions and facilitates global exploration of the search space.
6. Reproduction and Selection: Pelicans reproduce based on their foraging success, where the more successful individuals have a higher chance of passing their genetic material to the next generation. In the POA, the reproduction process involves selecting the fittest pelicans and generating new solutions through variation operators like mutation and crossover.
7. Iterative Process: The Pelican Optimization Algorithm iteratively updates the positions of the pelicans across multiple generations. With each iteration, the algorithm refines the solutions and strives to improve the overall fitness of the population.
8. Convergence and Termination: The algorithm aims to converge towards an optimal or near-optimal solution as the iterations progress. The termination criterion can be based on a maximum number of iterations, a threshold value for the fitness function, or a combination of both.
9. Applications: The Pelican Optimization Algorithm can be applied to a wide range of optimization problems, including engineering design, scheduling, data clustering, image processing, and more. It has shown promising results in various domains due to its ability to efficiently explore complex search spaces.


Hybrid Techniques

According to Arabi Nowdeh et al. [65], a hybrid method is any algorithm that combines two or more other algorithms to overcome the limitations of a single algorithm. Hybrid methods have emerged as a ground-breaking approach in various fields, combining the strengths of different techniques or methodologies to address complex problems and unlock new possibilities. By integrating diverse elements, such as technologies, theories, or strategies, hybrid

Corresponding author: Abba Muhammad Adua

✉ abbamuhammadadua@yahoo.com

Department of Electrical and Electronics Engineering, Faculty of Engineering, Kebbi State University of Science and Technology, Aliero.
© 2023. Faculty of Technology Education. ATBU Bauchi. All rights reserved



methods have shown immense potential in enhancing efficiency, improving outcomes, and fostering innovation [66]. This essay explores the concept of hybrid methods, their applications across domains, and the benefits they offer to solve challenges that require a multidimensional approach [37]. Numerous hybrid methods have been created in recent years to optimize hybrid systems, such as simulated Annealing and Chaotic Search (SA-CS) [67], chaotic search-harmony search-simulated annealing (CSHSSA), enhanced harmony search-based chaotic simulated annealing (IHSCSA), and harmony search-based simulated annealing (HSSA). Additionally, there are combinations of genetic algorithms and particle swarm optimization (GAPSO) [68], multi-objective crow search algorithm (MOCSA), [69], Monte Carlo simulation and multi-energy-balance/financial equations [70], and others.

A hybrid method is every method combining two or more algorithms, that allows

exploiting the advantages of these methods to overcome single algorithm drawbacks [65]. In genetic algorithm and particle swarm optimization (GAPSO), multi-objective crow search algorithm (MOCSA), Cluster Technique of Data Handling neural network and modified fruit fly optimization algorithm (GMDHM-FOA), and several supplementary hybrid methods. Hybrid methods have emerged as a powerful approach in diverse domains, offering a pathway to improved outcomes and innovation.

Table 4.1 showing the optimization techniques used in the analysis of Control and Sizing of Microgrids. The table identified and categorized the relevant optimization techniques discussed in the context of microgrids. Table 4.1 categorizes and describes various optimization techniques and their applications in the context of microgrids

Table 4.1: common optimization techniques typically used in microgrid control and sizing studies], [8], [9]:

Optimization Technique	Description	Application in Microgrids
Linear Programming (LP)	A method to achieve the best outcome in a mathematical model with linear relationships.	Used for cost minimization, scheduling, and resource allocation in microgrids.
Non-Linear Programming (NLP)	Optimization where some constraints or the objective function are non-linear.	Applied to handle non-linearities in power flow and renewable integration in microgrids.
Mixed-Integer Programming (MIP)	Combines integer and real variables in optimization problems.	Useful for unit commitment and economic dispatch problems in microgrids.
Dynamic Programming (DP)	Breaks down problems into simpler sub-problems and solves them recursively.	Employed for energy management and storage optimization in microgrids.
Stochastic Programming	Optimization under uncertainty, accounting for various scenarios and probabilities.	Manages uncertainties in load demand and renewable energy generation in microgrids.
Robust Optimization	Deals with optimization problems under uncertain but bounded parameters.	Ensures reliable operation of microgrids under uncertain conditions.
Heuristic Methods	Problem-solving approaches using practical methods not guaranteed to be optimal.	Includes genetic algorithms, particle swarm optimization, used for complex microgrid optimization problems.

Corresponding author: Abba Muhammad Adua

✉ abbamuhammaddua@yahoo.com

Department of Electrical and Electronics Engineering, Faculty of Engineering, Kebbi State University of Science and Technology, Alfero.

© 2023. Faculty of Technology Education. ATBU Bauchi. All rights reserved



Optimization Technique	Description	Application in Microgrids
Multi-Objective Optimization	Optimization involving more than one objective function.	Balances trade-offs between cost, reliability, and environmental impact in microgrids.
Game Theory	Mathematical study of strategic interaction among rational decision-makers.	Applied to distributed energy resource management and pricing strategies in microgrids.
Artificial Intelligence (AI)	Use of algorithms and machine learning for optimization.	Enhances predictive control, demand forecasting, and real-time optimization in microgrids.

COMPARISON BETWEEN OPTIMIZATION METHODS: UNVEILING THE PATH TO EFFICIENCY

Optimization methods play a crucial role in numerous fields, offering systematic approaches to finding optimal solutions for complex problems [72]. However, the selection of an appropriate optimization method depends on various factors such as problem characteristics, computational resources, and desired outcomes [73]. This essay aims to compare and contrast different optimization methods, shedding light on their strengths, limitations, and application domains. By understanding the nuances of each method, practitioners can make informed decisions and employ the most suitable approach for their specific optimization needs [7].

High performance, the ability to solve complicated problems, and the usage of multi-

objective functions are all characteristics of optimization methods [45]. The most prevalent drawbacks of all optimization methods are their complexity and length of time. The most effective strategy for economic optimization is the classical approach; however, the space available for optimization parameters is constrained [74]. Due to the complicated procedure and codes utilized, the artificial approach requires high hardware performance to function. The advantages of this method, however, include great efficiency and speed with good accuracy. Combining traditional and artificial methods demonstrates a way that is fast and reliable but also requires complicated design and is challenging to generate the proper code. Table 4.2 condenses the Benefits and weaknesses of the respective optimization methods:

Table 4.2: Advantages and drawbacks of each optimization method


Method	Advantages	Weaknesses
Classical method	✓ Enable solution for multi-objective problem	✓ Limited space optimization
	✓ Useful for investment decision	✓ Linearity about variables
	✓ Requires less time	✓ The method needs discrete and continuous probability
Artificial method	✓ Maximum efficiency level	✓ Complex solving process
	✓ Good calculation accuracy	✓ Required long-term memory space
	✓ High convergence speed	✓ Several changes are required.
Hybrid method	✓ Require less time	✓ Complexity in designing the system.
	✓ Most robustness	✓ Extended solutions
	✓ Quick convergence	✓ Difficulty in providing code

Corresponding author: Abba Muhammad Adua

✉ abbamuhammaddua@yahoo.com

Department of Electrical and Electronics Engineering, Faculty of Engineering, Kebbi State University of Science and Technology, Aliero.

© 2023. Faculty of Technology Education. ATBU Bauchi. All rights reserved



A. Gradient-Based Methods:

Gradient-based optimization methods, such as gradient descent and its variants, are widely employed in both linear and nonlinear optimization problems. They utilize derivative information to iteratively update the solution towards the direction of the steepest descent, aiming to converge to an optimal point. Key characteristics and considerations include:

- i. Strengths: These methods are computationally efficient, especially in high-dimensional spaces. They are well-suited for smooth, convex optimization problems and have a strong theoretical foundation.
- ii. Limitations: Gradient-based methods may struggle with non-convex problems, as they can get trapped in local optima. They also require the calculation of derivatives, which may be challenging or computationally expensive in some cases.

B. Evolutionary Algorithms:

Evolutionary algorithms, inspired by biological evolution, mimic the process of natural selection to search for optimal solutions. They operate on a population of candidate solutions and employ mechanisms such as mutation, crossover, and selection to iteratively improve the population over generations. Key characteristics and considerations include:

- i. Strengths: Evolutionary algorithms excel in solving complex, non-convex optimization problems, as they explore the solution space more extensively. They do not require derivative information, making them applicable to problems with non-differentiable or discontinuous objective functions.

- ii. Limitations: These methods can be computationally intensive, especially for large-scale problems, and may require significant computational resources. Convergence to optimal solutions might be slower compared to gradient-based methods, particularly in well-behaved, smooth problems.

C. Simulated Annealing:

Simulated annealing is a probabilistic optimization method that draws inspiration from the physical process of annealing in metallurgy. It employs a random search strategy that allows occasional uphill movements to escape local optima. Key characteristics and considerations include:

- i. Strengths: Simulated annealing is effective for problems with rugged, multi-modal landscapes, where traditional gradient-based methods may struggle. It provides a balance between exploration and exploitation, enabling the search to escape suboptimal solutions.
- ii. Limitations: The performance of simulated annealing is highly dependent on the cooling schedule and the temperature parameters. Setting these parameters correctly can be challenging, and improper choices may lead to suboptimal results. It may also require a larger number of function evaluations compared to gradient-based methods.

D. Particle Swarm Optimization:


Particle Swarm Optimization (PSO) is an optimization technique inspired by the social behavior of bird flocking or fish schooling. It employs a population of particles that move through the solution space, adjusting their positions based on their own best-known solution

Corresponding author: Abba Muhammad Adua

✉ abbamuhammaddua@yahoo.com

Department of Electrical and Electronics Engineering, Faculty of Engineering, Kebbi State University of Science and Technology, Alfero.

© 2023. Faculty of Technology Education. ATBU Bauchi. All rights reserved



and the collective knowledge of the swarm. Key characteristics and considerations include:

- i. Strengths: PSO is particularly suitable for continuous and discrete optimization problems with many local optima. It is relatively simple to implement and computationally efficient. It has shown effectiveness in dynamic optimization problems, where the optimum changes over time.
- ii. Limitations: PSO can suffer from premature convergence, where the swarm gets stuck in suboptimal regions. The performance may be sensitive to parameter settings, requiring careful tuning. It may struggle with high-dimensional problems or those with constraints.

Optimization methods are vital tools for solving complex problems and finding optimal solutions. The choice of an appropriate method depends on the problem.

CONTROL METHODS USED IN HYBRID RENEWABLE ENERGY SYSTEM

Hybrid renewable energy systems combine multiple sources of renewable energy to generate electricity efficiently and reliably [73]. To control and optimize the operation of these systems, various control methods are employed. Here are some common control methods used in hybrid renewable energy systems [33]:

1. Power Management Control: This control method focuses on managing the power flow between different energy sources, energy storage systems, and load demand [75]. It ensures that each energy source operates at its optimal point and balances the power generation and consumption in the system. Power management control

- algorithms can prioritize and allocate power based on factors such as availability, cost, and system efficiency [76].
2. Maximum Power Point Tracking (MPPT): MPPT is used in systems that involve solar photovoltaic (PV) panels and wind turbines. It tracks the maximum power point of each energy source to extract the maximum available power. MPPT algorithms adjust the operating conditions of renewable energy sources, such as the voltage or rotor speed, to ensure the system operates at the peak power output [4].
3. Energy Storage Control: Energy storage systems, such as batteries, are crucial components of hybrid renewable energy systems. They help store excess energy during periods of high generation and supply it during periods of low generation or high demand [77]. Energy storage control methods involve managing the charging and discharging cycles of the storage system, optimizing the energy flow, and maintaining the state of charge within specified limits [78].
4. Load Management Control: Load management control focuses on optimizing the utilization of energy in the system by coordinating and scheduling the operation of various loads. It aims to match the energy demand with the available renewable energy supply to minimize reliance on non-renewable sources [79]. Load management control algorithms can prioritize and schedule loads based on their priority, energy requirements, and available renewable energy resources [75].
5. Voltage and Frequency Control: In hybrid renewable energy systems, maintaining stable voltage and

Corresponding author: Abba Muhammad Adua

✉ abbamuhammadadua@yahoo.com

Department of Electrical and Electronics Engineering, Faculty of Engineering, Kebbi State University of Science and Technology, Aliero.
© 2023. Faculty of Technology Education. ATBU Bauchi. All rights reserved



frequency levels is essential for the reliable operation of electrical devices. Control methods are used to regulate voltage and frequency by adjusting the power output of the energy sources and coordinating their operation [21]. These methods ensure that the system operates within acceptable voltage and frequency limits under varying load conditions [4].

6. **Fault Detection and Protection:** Hybrid renewable energy systems require robust fault detection and protection mechanisms to prevent damage to the system components and ensure safe operation [80]. Control methods for fault detection monitor various parameters, such as voltage, current, and temperature, to identify abnormalities or malfunctions. Once a fault is detected, protection mechanisms such as circuit breakers or isolators can be activated to isolate the faulty component and prevent further damage [4].

These are some of the control methods commonly used in hybrid renewable energy systems. The specific control strategies and algorithms employed may vary depending on the system configuration, renewable energy sources involved, and the desired system performance. Continuous advancements in control technologies aim to improve the efficiency, reliability, and integration of renewable energy sources in hybrid systems. Generally, the most critical parameters

that should be controlled in every hybrid system [67] are as follows: Stability: This means the voltage and frequency of the system.

1. Protection: observing of power flow.
2. Power balance: optimal load distribution.

Secondary control of hybrid systems has been categorized by certain writers, into three main categories: centralized, distributed, and decentralized control. The division of control methods into two categories—classical control and intelligent control—was also made by [4]. There are numerous control strategies for wind turbines in the literature, including MPPT (Maximum power point tracking) based on practical swarm optimization (PSO), direct power control (DPC) based voltage vector selection on the rotor side converter, and robust sliding mode pitch control [84].

Intelligent techniques include the neural network algorithm, fuzzy logic controller, multi-objective particle swarm optimization (PSO) [85], and adaptive neuro-fuzzy inference system (ANFIS) [85]. These techniques are considered to be the classical methods. The majority of hybrid systems employ distributed or hybrid controls because these are efficient in decentralized control, minimize system failure, and allow for the use of various control types within a single hybrid system.

Table 4.2: Comparison of each method used in control methods

Method of control	Advantages	Drawbacks
Centralize	Minimization of power costs Can achieve global optimization.	Use a system based on one central control
Distributed	Low possibility of system failure Achieve low and medium use	Complex connection system Mostly suboptimal solutions

Corresponding author: Abba Muhammad Adua

✉ abbamuhammadadua@yahoo.com

Department of Electrical and Electronics Engineering, Faculty of Engineering, Kebbi State University of Science and Technology, Aliero.
© 2023. Faculty of Technology Education. ATBU Bauchi. All rights reserved

Method of control	Advantages	Drawbacks
Hybrid	Local optimization is achieved through centralized control Low use in local controllers	Complex control Complex potential in connection inside the system

HYBRID RENEWABLE ENERGY SYSTEM MANAGEMENT METHODS

Hybrid renewable energy systems combine two or more renewable energy sources to provide a more reliable and efficient energy generation solution. Managing such systems requires careful planning, integration, and control of different energy sources. To maximize system performance, the management of a hybrid system ensures high system efficiency and high reliability at the lowest possible cost to enable system supply throughout the year [82]. It also increases the lifetime of the elements and reduces economic parameters [28], [54].

Here are some management methods commonly used for hybrid renewable energy systems, which are classified into three types due to objective strategy:

1. Technical objective strategy;
1. Economic objective strategy
2. Techno-economic strategy objective.

Technical objective strategy

The increasing complexity and interconnectedness of modern organizations have prompted the adoption of hybrid management approaches, combining traditional hierarchical structures with agile methodologies. The technical objective strategy of hybrid management represents a novel framework that aims to optimize operational efficiency, innovation, and adaptability while leveraging advanced technological tools and methodologies [78].




Figure 4.1: Key features of technical objectives approaches

Corresponding author: Abba Muhammad Adua

✉ abbamuhammadadua@yahoo.com

Department of Electrical and Electronics Engineering, Faculty of Engineering, Kebbi State University of Science and Technology, Aliero.

© 2023. Faculty of Technology Education. ATBU Bauchi. All rights reserved




Figure 4.2: Main characteristics of economic objectives strategies [4]

ii. Economic objective strategy

Overall, the economic objective strategy of the hybrid method of microgrids focuses on optimizing energy costs, load balancing, energy storage integration, demand response, grid integration, and leveraging advanced algorithms and control systems [72]. By combining these elements, the hybrid method aims to ensure efficient and economically viable operation of microgrids while fostering a transition to a more sustainable and resilient energy future.

iii. Techno-economic objective strategy

The techno-economic objective strategy of the hybrid method of microgrids is a comprehensive approach that aims to optimize the technical and economic aspects of microgrid systems [29]. It involves the integration of different energy sources, such as renewable energy and conventional power generation, to ensure reliable and cost-effective electricity supply to a localized area.




Figure 4.3: Main characteristics of techno-economic objectives strategies

Corresponding author: Abba Muhammad Adua

✉ abbamuhammadadua@yahoo.com

Department of Electrical and Electronics Engineering, Faculty of Engineering, Kebbi State University of Science and Technology, Aliero.

© 2023. Faculty of Technology Education. ATBU Bauchi. All rights reserved



This approach, which incorporates technical and economic characteristics, is based on nonlinear optimization to solve multi-objective functions [67]. The benefit of this method is that it lowers economic factors like global cost while increasing technical parameters like component performance and lifetime [8].

Energy Management System in Microgrid

An energy management system (EMS) plays a crucial role in optimizing the operation and control of microgrids. As self-contained power systems that can operate independently or in conjunction with the main grid, microgrids require efficient management to ensure a reliable, cost-effective, and sustainable energy supply [7]. Few scholars have recently attempted to review the EM characteristics of MGs by concentrating on their concept. Energy management (EM) is the act of keeping track of, organizing, maximizing, and conserving energy to create an energy-efficient system [53].

Classification of Energy Management System for Microgrids

An EMS in MG can be categorized broadly into three categories based on supervisory control, operating time platform, and the decision-making approach used to accomplish the effective and optimal operation of MG.

i. EMS based on supervisory control

This can be defined as the comprehensive monitoring of the individual process processes taking place in the system. It is also responsible for the efficient connectivity between individual controllers. EMS can be roughly classified into three forms based on supervisory control: centralized, decentralized as well and distributed. The centralized EMS is made up of a central controller that compiles all the required data about DERs, loads, the electrical market, weather, etc., and conducts the best scheduling of MG. [53]. Decentralized EMS utilizes numerous central controllers that interact in real-time with each other and their LCs. Every LC submits to the central controller a demand request for the current and upcoming generations. Additionally, it executes

the best scheduling and relays that information to the LC of the MG [69].

This process continues until local and global goals are met. The third strategy distributed EMS, eliminates the idea of centralization and is a more sophisticated form of decentralized EMS [28]. Each LC unit in this control strategy interacts with the central controller and each other to exchange local data such as voltage and frequency [29].

Decentralized supervisory control approaches refer to a set of techniques and methodologies used in control systems to distribute decision-making and supervisory tasks across multiple entities or agents. These approaches are commonly employed in complex systems where a centralized control architecture may not be feasible or desirable. In decentralized supervisory control, decision-making authority is distributed among multiple agents or subsystems. Each agent is responsible for monitoring and controlling a specific part of the system, while also coordinating with other agents to achieve the overall system objectives [11].

ii. EMS based on the operating time platform

An Energy Management System (EMS) based on the operating time platform is a concept related to energy management and control in various domains, particularly in the context of electricity grids and power distribution systems. It involves utilizing the operating time of energy-consuming devices or equipment as a basis for optimizing energy usage and improving overall system efficiency. Here are some details about an EMS based on the operating time platform [11].


iii. EMS based on the offline time platform

EMS (Energy Management System) based on the offline time platform refers to a software or system that helps manage and optimize energy consumption in a facility or organization using data collected during offline periods. Here are some details about this concept. Overall, an EMS based on the offline time platform is a powerful tool that leverages data collected

Corresponding author: Abba Muhammad Adua

✉ abbamuhammadadua@yahoo.com

Department of Electrical and Electronics Engineering, Faculty of Engineering, Kebbi State University of Science and Technology, Aliero.
© 2023. Faculty of Technology Education. ATBU Bauchi. All rights reserved



during periods of inactivity or low energy demand to drive energy efficiency and cost savings. By analyzing energy patterns and implementing optimization strategies, organizations can effectively manage their energy consumption and contribute to a more sustainable future [53], ([37], Additionally, the complex design of the EMS is a result of the high level of unpredictability in RERs and load demand [7].

FINDINGS FROM THE LITERATURE REVIEW

One prominent finding from the literature review on the "Control and Sizing of Microgrids" is the significant impact of renewable energy integration on microgrid control and sizing strategies. The increasing adoption of renewable energy sources, such as solar photovoltaics (PV) and wind turbines, within microgrids has introduced both opportunities and challenges for effective control and optimal sizing of microgrid systems.

CONCLUSION

In conclusion, the control and sizing of microgrids represent a critical and evolving field in the realm of modern energy systems. This paper has highlighted the current challenges faced in designing and managing microgrids, discussed various control approaches that have been proposed and implemented to address these challenges, and provided insights into the future directions of this dynamic field. As the world continues to transition towards more decentralized and sustainable energy systems, the optimization of microgrid control and sizing will play a pivotal role in ensuring reliable, resilient, and environmentally friendly power generation and distribution. To meet the growing demand for clean energy, it is imperative that researchers, industry experts, and policymakers collaborate to overcome existing obstacles and innovate new solutions, ultimately paving the way for a more efficient and sustainable energy future.

RECOMMENDATIONS FOR FUTURE RESEARCH

Research on the control and sizing of microgrids is a rapidly evolving field with


significant implications for the future of sustainable energy systems. To contribute to the ongoing progress in this area, here are some recommendations for future research:

1. Integration of Renewable Energy Sources: Investigate advanced control strategies for the seamless integration of various renewable energy sources (e.g., solar, wind, hydro) into microgrids, considering the intermittent nature of these sources.
2. Energy Storage Optimization: Explore optimization techniques for sizing and controlling energy storage systems within microgrids. This includes determining the optimal type, capacity, and placement of energy storage devices to enhance grid stability and reliability.
3. Demand Response Integration: Investigate the integration of demand response programs into microgrid control, enabling better coordination between energy supply and demand while considering the preferences and behaviors of end-users.
4. Cybersecurity and Resilience: Focus on enhancing the cybersecurity of microgrid control systems to protect against cyber threats and ensure the resilience of microgrid operations in the face of attacks or disruptions.
5. Distributed Control Architectures: Explore distributed control strategies, such as multi-agent systems and decentralized control, to improve the scalability and robustness of microgrid control systems.
6. Grid-Interactive Buildings: Investigate the role of grid-interactive buildings in microgrids, exploring how building energy management systems can contribute to grid stability and optimization.
7. Machine Learning and AI: Explore the application of machine learning and artificial intelligence techniques for

Corresponding author: Abba Muhammad Adua

✉ abbamuhammadadua@yahoo.com

Department of Electrical and Electronics Engineering, Faculty of Engineering, Kebbi State University of Science and Technology, Alifero.
© 2023. Faculty of Technology Education. ATBU Bauchi. All rights reserved



- predictive maintenance, fault detection, and load forecasting within microgrids.
8. Microgrid Market Models: Develop models and frameworks for microgrid market design and operation, considering various stakeholders, pricing mechanisms, and regulatory policies.
 9. Multi-Energy Systems: Investigate the integration of multiple energy carriers (e.g., electricity, heat, gas) within microgrids, aiming for holistic energy management and optimization.
 10. Environmental and Economic Assessment: Conduct comprehensive assessments of the environmental and economic impacts of microgrid deployment, considering factors like greenhouse gas emissions, cost-effectiveness, and societal benefits.
 11. Standardization and Interoperability: Work on establishing industry standards and protocols to ensure the interoperability of different microgrid components and systems, promoting greater adoption and integration.
 12. Real-World Demonstrations: Conduct field trials and real-world demonstrations of advanced microgrid control strategies to validate their performance and gather practical insights.
 13. Community Microgrids: Investigate the design and operation of community-scale microgrids, considering the unique challenges and opportunities they present in terms of control and sizing.
 14. Resilience in Extreme Conditions: Explore methods to enhance microgrid resilience during extreme weather events, natural disasters, and other emergencies.
 15. Social and Behavioral Aspects: Investigate the social and behavioral aspects of microgrid adoption, including user acceptance, community

engagement, and the impact on quality of life.

These recommendations encompass a wide range of research areas within the control and sizing of microgrids, reflecting the multidisciplinary nature of this field and its critical importance in transitioning toward a more sustainable and resilient energy future. Researchers can contribute significantly to addressing current challenges and shaping the future of microgrid technology.

REFERENCES

- [1] H. A. Muqeet, H. M. Munir, H. Javed, M. Shahzad, M. Jamil, and J. M. Guerrero, "An Energy Management System of Campus Microgrids : State-of-the-Art and Future Challenges," 2021.
- [2] G. Li, Y. Chen, A. Luo, and H. Wang, "An Enhancing Grid Stiffness Control Strategy of STATCOM/BESS for Damping Sub-Synchronous Resonance in Wind Farm Connected to Weak Grid," *IEEE Trans. Ind. Informatics*, vol. 16, no. 9, pp. 5835–5845, Sep. 2020, doi: 10.1109/TII.2019.2960863.
- [3] F. Conteh, H. Takahashi, A. M. Hemeida, N. Krishnan, A. Mikhaylov, and T. Senjyu, "Analysis of hybrid grid-connected renewable power generation for sustainable electricity supply in sierra leone," *Sustain.*, vol. 13, no. 20, 2021, doi: 10.3390/su132011435.
- [4] B. Belabbas, T. Allaoui, M. Tadjine, and M. Denai, "Power management and control strategies for off-grid hybrid power systems with renewable energies and storage," *Energy Syst.*, vol. 10, no. 2, pp. 355–384, May 2019, doi: 10.1007/s12667-017-0251-y.
- [5] N. Nikolaev, K. Dimitrov, and Y. Rangelov, "A comprehensive review of small-signal stability and power oscillation damping through photovoltaic inverters," *Energies*, vol.

Corresponding author: Abba Muhammad Adua

✉ abbamuhammadadua@yahoo.com

Department of Electrical and Electronics Engineering, Faculty of Engineering, Kebbi State University of Science and Technology, Aliero.
© 2023. Faculty of Technology Education. ATBU Bauchi. All rights reserved



- 14, no. 21, 2021, doi: 10.3390/en14217372.
- [6] Y. Chen, S. M. Mazhari, C. Y. Chung, S. O. Faried, and B. C. Pal, "Rotor Angle Stability Prediction of Power Systems with High Wind Power Penetration Using a Stability Index Vector," *IEEE Trans. Power Syst.*, vol. 35, no. 6, pp. 4632–4643, 2020, doi: 10.1109/TPWRS.2020.2989725.
- [7] A. L. Bukar, C. W. Tan, L. K. Yiew, R. Ayop, and W. S. Tan, "A rule-based energy management scheme for long-term optimal capacity planning of grid-independent microgrid optimized by multi-objective grasshopper optimization algorithm," *Energy Convers. Manag.*, vol. 221, no. June, p. 113161, 2020, doi: 10.1016/j.enconman.2020.113161.
- [8] A. V. Kumar, S. Sharma, and A. Verma, "Optimal sizing and multi-energy management strategy for PV-biofuel-based off-grid systems," *IET Smart Grid*, vol. 3, no. 1, pp. 83–97, Feb. 2020, doi: 10.1049/iet-stg.2019.0178.
- [9] H. Wei, Z. Hongxuan, D. Yu, W. Yiting, D. Ling, and X. Ming, "Short-term optimal operation of hydro-wind-solar hybrid system with improved generative adversarial networks," *Appl. Energy*, vol. 250, no. January, pp. 389–403, 2019, doi: 10.1016/j.apenergy.2019.04.090.
- [10] V. Veerasamy *et al.*, "Automatic load frequency control of a multi-area dynamic interconnected power system using a hybrid PSO-GSA-Tuned PID controller," *Sustain.*, vol. 11, no. 24, 2019, doi: 10.3390/su11246908.
- [11] S. D. Rodrigues and V. J. Garcia, "Transactive energy in microgrid communities: A systematic review," *Renew. Sustain. Energy Rev.*, vol. 171, no. October 2022, p. 112999, 2023, doi: 10.1016/j.rser.2022.112999.
- [12] H. Hizam, "Artificial Neural Networks , PID , and Fuzzy Logic Controllers," 2022.
- [13] H. Setiadi, N. Mithulanathan, R. Shah, K. Y. Lee, and A. U. Krismanto, "Resilient wide-area multi-mode controller design based on Bat algorithm for power systems with renewable power generation and battery energy storage systems," *IET Gener. Transm. Distrib.*, vol. 13, no. 10, pp. 1884–1894, 2019, doi: 10.1049/iet-gtd.2018.6384.
- [14] S. Shahzad, M. A. Abbasi, H. Ali, M. Iqbal, R. Munir, and H. Kilic, "Possibilities, Challenges, and Future Opportunities of Microgrids: A Review," *Sustain.*, vol. 15, no. 8, 2023, doi: 10.3390/su15086366.
- [15] Y. Zhang, T. Ma, and H. Yang, "Grid-connected photovoltaic battery systems: A comprehensive review and perspectives," *Appl. Energy*, vol. 328, p. 120182, Dec. 2022, doi: 10.1016/J.APENERGY.2022.120182.
- [16] O. O. Mohammed, A. O. Otuoze, S. Salisu, O. Ibrahim, and N. A. Rufa'i, "Virtual synchronous generator: an overview," *Niger. J. Technol.*, vol. 38, no. 1, p. 153, 2019, doi: 10.4314/njt.v38i1.20.
- [17] D. Jain and D. Saxena, "Comprehensive review on control schemes and stability investigation of hybrid AC-DC microgrid," *Electr. Power Syst. Res.*, vol. 218, p. 109182, May 2023, doi: 10.1016/J.EPSR.2023.109182.
- [18] R. Yousefian and S. Kamalasadani, "A Review of Neural Network Based Machine Learning Approaches for Rotor Angle Stability Control," pp. 1–14, 2017.
- [19] B. Ismail, N. I. Abdul Wahab, M. L. Othman, M. A. M. Radzi, K. Naidu Vijyakumar, and M. N. Mat Naain, "A Comprehensive Review on Optimal Location and Sizing of Reactive Power

Corresponding author: Abba Muhammad Adua

✉ abbamuhammadadua@yahoo.com

Department of Electrical and Electronics Engineering, Faculty of Engineering, Kebbi State University of Science and Technology, Aliero.

© 2023. Faculty of Technology Education. ATBU Bauchi. All rights reserved



- [20] M. Saadatmand, B. Mozafari, G. B. Gharehpetian, and S. Soleymani, "Optimal coordinated tuning of power system stabilizers and wide-area measurement-based fractional-order PID controller of large-scale PV farms for LFO damping in smart grids," *Int. Trans. Electr. Energy Syst.*, vol. 31, no. 2, pp. 1–19, 2021, doi: 10.1002/2050-7038.12612.
- [21] R. Perez, M. Rivera, P. Wheeler, G. Mirzaeva, E. E. Espinosa, and J. A. Rohten, "Microgrid Power Sharing Framework for Software Defined Networking and Cybersecurity Analysis," *IEEE Access*, vol. 10, no. August, pp. 111389–111405, 2022, doi: 10.1109/ACCESS.2022.3215434.
- [22] M. G. and V. Loksha, "Geothermal Handbook : Planning and Financing Power Generation," *World Bank Tech. Rep.*, vol. 002/12, pp. 1–164, 2002.
- [23] A. Akbari-Dibavar, S. Nojavan, and K. Zare, "Optimal Sizing and Sizing of Energy Storage Systems in a Smart Distribution Network Considering Network Constraints and Demand Response Program," *Res. Artic. J. Energy Manag. Technol.*, vol. 3, no. 2, p. 14, doi: 10.22109/jemt.2018.143478.1115.
- [24] L. Controller, "DC Link Voltage Enhancement in DC Microgrid Using PV Based High Gain Converter with Cascaded Fuzzy," 2023.
- [25] M. M. Gamil *et al.*, "Optimal Multi-Objective Power Scheduling of a Residential Microgrid Considering Renewable Sources and Demand Response Technique," *Sustainability*, vol. 10, no. 33, p. 90, 2022, doi: <https://doi.org/10.3390/su142113709>.
- [26] B. Jyoti Saharia, H. Brahma, and N. Sarmah, "A review of algorithms for control and optimization for energy management of hybrid renewable energy systems," *J. Renew. Sustain. Energy*, vol. 10, no. 5, 2018, doi: 10.1063/1.5032146.
- [27] M. Wiatros-Motyka, D. Jones, H. Broadbent, N. Fulghum, R. Dizon, and P. MacDonald, "Global Electricity Mid-Year Insights 2022," no. October, 2022.
- [28] S. Leonori, M. Paschero, F. M. Frattale Mascioli, and A. Rizzi, "Optimization strategies for Microgrid energy management systems by Genetic Algorithms," *Appl. Soft Comput. J.*, vol. 86, p. 105903, 2020, doi: 10.1016/j.asoc.2019.105903.
- [29] C. Ammari, D. Belatrache, B. Touhami, and S. Makhloufi, "Sizing, optimization, control and energy management of hybrid renewable energy system—A review," *Energy Built Environ.*, vol. 3, no. 4, pp. 399–411, 2022, doi: 10.1016/j.enbenv.2021.04.002.
- [30] N. M. Khattab, M. A. Badr, E. Tawfik El Shenawy, H. H. Sharawy, and M. S. Shalaby, "Economic Analysis of Stand-Alone Hybrid Wind/PV/Diesel Water Pumping System: A Case Study in Egypt," *Model. Simul. Optim. Wind Farms Hybrid Syst.*, pp. 1–19, 2020, doi: 10.5772/intechopen.89161.
- [31] S. K. A. Shezan, S. S. Ali, Z. Rahman, and Rawdah, "Design and implementation of an islanded hybrid microgrid system for a large resort center for Penang Island with the proper application of excess energy," *Environ. Prog. Sustain. Energy*, vol. 40, no. 4, Jul. 2021, doi: 10.1002/ep.13584.
- [32] O. D. T. Odou, R. Bhandari, and R. Adamou, "Hybrid off-grid renewable power system for sustainable rural electrification in Benin," *Renew.*

Corresponding author: Abba Muhammad Adua

✉ abbamuhammadadua@yahoo.com

Department of Electrical and Electronics Engineering, Faculty of Engineering, Kebbi State University of Science and Technology, Aliero.

© 2023. Faculty of Technology Education. ATBU Bauchi. All rights reserved



- [33] *Energy*, vol. 145, pp. 1266–1279, 2020, doi: 10.1016/j.renene.2019.06.032.
A. A. Khan, A. F. Minai, R. K. Pachauri, and H. Malik, “Optimal Sizing, Control, and Management Strategies for Hybrid Renewable Energy Systems: A Comprehensive Review,” *Energies*, vol. 15, no. 17, p. 6249, Aug. 2022, doi: 10.3390/en15176249.
- [34] S. A. HASEN, Ş. SÖNMEZ, and S. AYASUN, “Enhancement of stability delay margins by virtual inertia control for microgrids with time delay,” *Turkish J. Electr. Eng. Comput. Sci.*, vol. 30, no. 6, pp. 2221–2236, 2022, doi: 10.55730/1300-0632.3935.
- [35] M. A. Yazdanpanah, “Modeling and sizing optimization of hybrid photovoltaic/wind power generation system,” *J. Ind. Eng. Int.*, vol. 10, no. 1, 2014, doi: 10.1007/s40092-014-0049-7.
- [36] H. Karimi, G. B. Gharehpetian, R. Ahmadihangar, and A. Rosin, “Optimal energy management of grid-connected multi-microgrid systems considering demand-side flexibility: A two-stage multi-objective approach,” *Electr. Power Syst. Res.*, vol. 214, no. PA, p. 108902, 2023, doi: 10.1016/j.epsr.2022.108902.
- [37] S. Moghaddam, M. Bigdeli, and M. Moradlou, “Optimal design of an off-grid hybrid renewable energy system considering generation and load uncertainty: the case of Zanjan city, Iran,” *SN Appl. Sci.*, vol. 3, no. 8, Aug. 2021, doi: 10.1007/s42452-021-04718-x.
- [38] J. A. Momoh and S. S. Reddy, “Review of optimization techniques for Renewable Energy Resources,” *PEMWA 2014 - 2014 IEEE Symp. Power Electron. Mach. Wind Water Appl.*, vol. 8, no. 1, pp. 13–30, 2014, doi: 10.1109/PEMWA.2014.6912225.
- [39] Y. Sawle, S. C. Gupta, and A. K. Bohre, “PV-wind hybrid system: A review with case study,” *Cogent Eng.*, vol. 3, no. 1, pp. 1–31, 2016, doi: 10.1080/23311916.2016.1189305.
- [40] M. Razaq, B. A. Basit, S. A. Q. Mohammed, and J. W. Jung, “A comprehensive state-of-the-art review of power conditioning systems for energy storage systems: Topology and control applications in power systems,” *IET Renew. Power Gener.*, vol. 16, no. 10, pp. 1971–1991, 2022, doi: 10.1049/rpg2.12498.
- [41] U. Akram, M. Khalid, and S. Shafiq, “Optimal sizing of a wind/solar/battery hybrid grid-connected microgrid system,” *IET Renew. Power Gener.*, vol. 12, no. 1, pp. 72–80, Jan. 2018, doi: 10.1049/iet-rpg.2017.0010.
- [42] J. C. Kurnia, Z. A. Putra, O. Muraza, S. A. Ghoreishi-Madiseh, and A. P. Sasmito, “Numerical evaluation, process design and techno-economic analysis of geothermal energy extraction from abandoned oil wells in Malaysia,” *Renew. Energy*, vol. 175, pp. 868–879, 2021, doi: 10.1016/j.renene.2021.05.031.
- [43] BP, “Statistical Review of World Energy globally consistent data on world energy markets and authoritative publications in the field of energy,” *BP Energy Outlook*, vol. 70, p. 72, 2021.
- [44] T. Rahkar Farshi, “Battle royale optimization algorithm,” *Neural Comput. Appl.*, vol. 33, no. 4, pp. 1139–1157, 2021, doi: 10.1007/s00521-020-05004-4.
- [45] P. Trojovský and M. Dehghani, “Pelican Optimization Algorithm: A Novel Nature-Inspired Algorithm for Engineering Applications,” *Sensors*, vol. 22, no. 3, pp. 1–34, 2022, doi: 10.3390/s22030855.
- [46] S. Kaur, L. K. Awasthi, A. L. Sangal, and G. Dhiman, “Tunicate Swarm Algorithm: A new bio-inspired based metaheuristic paradigm for global optimization,” *Eng. Appl. Artif. Intell.*,

Corresponding author: Abba Muhammad Adua

✉ abbamuhammadadua@yahoo.com

Department of Electrical and Electronics Engineering, Faculty of Engineering, Kebbi State University of Science and Technology, Aliero.
© 2023. Faculty of Technology Education. ATBU Bauchi. All rights reserved



- [47] vol. 90, no. February, p. 103541, 2020, doi: 10.1016/j.engappai.2020.103541.
F. A. Hashim, E. H. Houssein, K. Hussain, M. S. Mabrouk, and W. Al-Atabany, "Honey Badger Algorithm: New metaheuristic algorithm for solving optimization problems," *Math. Comput. Simul.*, vol. 192, pp. 84–110, 2022, doi: 10.1016/j.matcom.2021.08.013.
- [48] A. Shah, S. N. Pandey, V. Vishal, and S. K. Saha, "Modeling of heat transfer in abandoned oil and gas wells," *Work. Geotherm. Reserv. Eng.*, no. February, pp. 1–8, 2019.
- [49] A. S. Alghamdi, "Optimal Power Flow of Hybrid Wind/Solar/Thermal Energy Integrated Power Systems Considering Costs and Emissions via a Novel and Efficient Search Optimization Algorithm," *Appl. Sci.*, vol. 13, no. 8, 2023, doi: 10.3390/app13084760.
- [50] K. Shivam, J. Tzou, and S. Wu, "Multi-Objective Sizing Optimization of a Grid-Connected Solar – Wind Hybrid System Using Climate Classification : A Case Study of Four," 2020.
- [51] S. Sukumar, H. Mokhlis, S. Mekhilef, K. Naidu, and M. Karimi, "Mix-mode energy management strategy and battery sizing for economic operation of grid-tied microgrid," *Energy*, vol. 118, pp. 1322–1333, 2017, doi: 10.1016/j.energy.2016.11.018.
- [52] P. W. Sauer, M. A. Pai, and J. H. Chow, *Power System Dynamics and Stability: With Synchrophasor Measurement and Power System Toolbox 2e*. 2017. doi: 10.1002/9781119355755.
- [53] P. Sharma, H. Dutt Mathur, P. Mishra, and R. C. Bansal, "A critical and comparative review of energy management strategies for microgrids," *Appl. Energy*, vol. 327, no. September, p. 120028, 2022, doi: 10.1016/j.apenergy.2022.120028.
- [54] X. Lu and H. Wang, "Optimal Sizing and Energy Management for Cost-Effective PEV Hybrid Energy Storage Systems," *IEEE Trans. Ind. Informatics*, vol. 16, no. 5, pp. 3407–3416, May 2020, doi: 10.1109/TII.2019.2957297.
- [55] Y. Huang, W. Wang, and B. Hou, "A hybrid algorithm for mixed integer nonlinear programming in residential energy management," *J. Clean. Prod.*, vol. 226, pp. 940–948, 2019, doi: 10.1016/j.jclepro.2019.04.062.
- [56] J. L. Torres-Madroño, C. Nieto-Londoño, and J. Sierra-Pérez, "Hybrid energy systems sizing for the colombian context: A genetic algorithm and particle swarm optimization approach," *Energies*, vol. 13, no. 21, pp. 1–30, 2020, doi: 10.3390/en13215648.
- [57] T. F. Sterkenburg and P. D. Grünwald, "The no-free-lunch theorems of supervised learning," *Synthese*, vol. 199, no. 3–4, pp. 9979–10015, 2021, doi: 10.1007/s11229-021-03233-1.
- [58] A. G. Gad, *Particle Swarm Optimization Algorithm and Its Applications: A Systematic Review*, vol. 29, no. 5. Springer Netherlands, 2022. doi: 10.1007/s11831-021-09694-4.
- [59] S. M. Elghamrawy and A. E. Hassanien, "A hybrid Genetic–Grey Wolf Optimization algorithm for optimizing Takagi–Sugeno–Kang fuzzy systems," *Neural Comput. Appl.*, vol. 34, no. 19, pp. 17051–17069, 2022, doi: 10.1007/s00521-022-07356-5.
- [60] S. Kaur, Y. Kumar, A. Koul, and S. Kumar, *A Systematic Review on Metaheuristic Optimization Techniques for Feature Selections in Disease Diagnosis : Open Issues and Challenges*, vol. 30, no. 3. Springer Netherlands, 2023. doi: 10.1007/s11831-022-09853-1.
- [61] F. A. Al-durzi and N. H. Al-nuaimi, "Load Frequency Control Using Artificial Intelligent Techniques for A Single Area Power System Load Frequency Control Using Artificial

Corresponding author: Abba Muhammad Adua

✉ abbamuhammadadua@yahoo.com

Department of Electrical and Electronics Engineering, Faculty of Engineering, Kebbi State University of Science and Technology, Aliero.
© 2023. Faculty of Technology Education. ATBU Bauchi. All rights reserved



- Intelligent Techniques for A Single Area Power System," *Researchgate*, vol. 33, no. 71, pp. 1–9, 2019.
- [62] M. A. Laughton and D. J. Warne, *Electrical Engineer 's Reference Book*. 2003.
- [63] W. Li, R. Wang, T. Zhang, M. Ming, and H. Lei, "Multi-scenario microgrid optimization using an evolutionary multi-objective algorithm," *Swarm Evol. Comput.*, vol. 50, no. July, p. 100570, 2019, doi: 10.1016/j.swevo.2019.100570.
- [64] L. Xing, J. Cai, X. Liu, J. Fang, and Y. Tian, "Distributed Secondary Control of DC Microgrid via the Averaging of Virtual Current Derivatives," 2023, doi: 10.1109/TIE.2023.3269470.
- [65] S. Arabi Nowdeh *et al.*, "Fuzzy multi-objective placement of renewable energy sources in distribution system with objective of loss reduction and reliability improvement using a novel hybrid method," *Appl. Soft Comput. J.*, vol. 77, pp. 761–779, 2019, doi: 10.1016/j.asoc.2019.02.003.
- [66] K. Anoune, M. Bouya, A. Astito, and A. Ben Abdellah, "Sizing methods and optimization techniques for PV-wind based hybrid renewable energy system: A review," *Renew. Sustain. Energy Rev.*, vol. 93, no. October 2017, pp. 652–673, 2018, doi: 10.1016/j.rser.2018.05.032.
- [67] M. W. Hasan and N. H. Abbas, "An improved swarm intelligence algorithms-based nonlinear fractional order-PID controller for a trajectory tracking of underwater vehicles," *Telkomnika (Telecommunication Comput. Electron. Control.)*, vol. 18, no. 6, pp. 3173–3183, 2020, doi: 10.12928/TELKOMNIKA.v18i6.16282.
- [68] M. Talaat, A. Y. Hatata, A. S. Alsayyari, and A. Alblawi, "A smart load management system based on the grasshopper optimization algorithm using the under-frequency load shedding approach," *Energy*, vol. 190, p. 116423, 2020, doi: 10.1016/j.energy.2019.116423.
- [69] N. Alamir, S. Kamel, T. F. Megahed, M. Hori, and S. M. Abdelkader, "Developing Hybrid Demand Response Technique for Energy Management in Microgrid Based on Pelican Optimization Algorithm," *Electr. Power Syst. Res.*, vol. 214, no. PA, p. 108905, 2023, doi: 10.1016/j.epsr.2022.108905.
- [70] M. Dong *et al.*, "Uncertainty and global sensitivity analysis of leveled cost of energy in wind power generation," *Energy Convers. Manag.*, vol. 229, no. October 2020, pp. 1–14, 2021, doi: 10.1016/j.enconman.2020.113781.
- [71] Y. Bai, J. Li, H. He, R. C. Dos Santos, and Q. Yang, "Optimal Design of a Hybrid Energy Storage System in a Plug-In Hybrid Electric Vehicle for Battery Lifetime Improvement," *IEEE Access*, vol. 8, pp. 142148–142158, 2020, doi: 10.1109/ACCESS.2020.3013596.
- [72] H. Fontenot and B. Dong, "Modeling and control of building-integrated microgrids for optimal energy management – A review," *Appl. Energy*, vol. 254, no. April, p. 113689, 2019, doi: 10.1016/j.apenergy.2019.113689.
- [73] S. Ali, Z. Zheng, M. Aillerie, J. P. Sawicki, M. C. Péra, and D. Hissel, "A review of dc microgrid energy management systems dedicated to residential applications," *Energies*, vol. 14, no. 14, pp. 1–26, 2021, doi: 10.3390/en14144308.
- [74] A. Mallick, A. Mishra, A. R. Hota, and P. Bajpai, "Distributed Coordination of Multi-Microgrids in Active Distribution Networks for Provisioning Ancillary Services," pp. 1–10, 2023, [Online]. Available: <http://arxiv.org/abs/2305.04456>
- [75] A. A. Kamel, H. Rezk, N. Shehata, and J. Thomas, "Energy management of a

Corresponding author: Abba Muhammad Adua

✉ abbamuhammadadua@yahoo.com

Department of Electrical and Electronics Engineering, Faculty of Engineering, Kebbi State University of Science and Technology, Aliero.

© 2023. Faculty of Technology Education. ATBU Bauchi. All rights reserved



- [76] dc microgrid composed of photovoltaic/fuel cell/battery/supercapacitor systems," *Batteries*, vol. 5, no. 3, pp. 1–26, 2019, doi: 10.3390/BATTERIES5030063.
- [77] J. Yan, X. Zhu, and N. Lu, "Smart hybrid house test systems in a solid-state transformer supplied microgrid," *IEEE Power Energy Soc. Gen. Meet.*, vol. 2015-Septe, pp. 1–5, 2015, doi: 10.1109/PESGM.2015.7286550.
- [78] A. Saha, P. Dash, N. R. Babu, T. Chiranjeevi, B. Venkateswararao, and Ł. Knypiński, "Impact of Spotted Hyena Optimized Cascade Controller in Load Frequency Control of Wave-Solar-Double Compensated Capacitive Energy Storage Based Interconnected Power System," *Energies*, vol. 15, no. 19, p. 6959, 2022, doi: 10.3390/en15196959.
- [79] P. Roy, J. He, T. Zhao, and Y. V. Singh, "Recent Advances of Wind-Solar Hybrid Renewable Energy Systems for Power Generation: A Review," *IEEE Open Journal of the Industrial Electronics Society*, vol. 3. Institute of Electrical and Electronics Engineers Inc., pp. 81–104, 2022. doi: 10.1109/OJIES.2022.3144093.
- [79] A. F. Bendary and M. M. Ismail, "Battery charge management for hybrid PV/wind/fuel cell with storage battery," *Energy Procedia*, vol. 162, pp. 107–116, 2019, doi: 10.1016/j.egypro.2019.04.012.

Corresponding author: Abba Muhammad Adua

✉ abbamuhammadadua@yahoo.com

Department of Electrical and Electronics Engineering, Faculty of Engineering, Kebbi State University of Science and Technology, Aliero.

© 2023. Faculty of Technology Education. ATBU Bauchi. All rights reserved